


Colour code of electronic	Pos.	Description
C1	C 8	Connector, 8-pin
C3	F 6	Connector, 21-pin
C3	E 3	Connector, 21-pin
C3	E 4	Connector, 21-pin
C3	E 2	Connector, 21-pin
C5	B 6	Connector, 2-pin
C9	D 5	Connector, 21-pin
C9	E 8	Connector 21-pin, front-Roof
C9	E 5	Connector 21-pin, front-Roof
C9	E 3	Connector 21-pin, front-Roof
C9	E 7	Connector 21-pin, front-Roof
C9	F 2	Connector, 21-pin
C84	F 3	Connector, 21-pin
C10	F 3	Connector, 21-pin
C10	F 2	Connector, 21-pin
C17	D 7	Splice, survivor, VIS
C18	B 6	Splice, survivor, VIS
C18	B 6	Splice, survivor, VIS
C40 A	D 8	Splice, survivor, VIS
C40 B	D 8	Splice, survivor, VIS
C141	B 5	Splice, survivor, VIS
C142	B 5	Splice, survivor, VIS
C142	B 1	Splice, survivor, VIS
C168	B 5	Splice, survivor, VIS
C207	D 3	Connector, splice, VIS
C208	D 2	Connector, splice, VIS
C251	A 4	Cut cable, VIS
C254	A 5	Cut cable, VIS
C256	A 4	Cut cable, VIS
C257	A 5	Cut cable, VIS
C258	D 4	Connector, splice, VIS
C488	E 6	Splice, survivor, VIS
C492	B 2	Splice, 7-pin, 24V
G9	F 2	Joint connector, ground
G9	F 3	Joint connector, ground
G9	F 6	Joint connector, ground
G10 E	E 2	Joint connector, ground
G10 F	E 4	Ground, roof
G10 F	E 3	Ground, roof
G13 G	B 2	Ground, beyond wall
G19 A	E 7	Ground, roof
G21 A	B 8	Ground, cab front
G21 B	B 8	Ground, cab front
G22 A	B 7	Ground, cab front
G22 B	B 7	Ground, cab front
G22 C	B 7	Ground, cab front
G22 C	C 5	Ground, cab front
L11	A 5	Distance light
L12	A 5	Distance light
L13	A 5	Front fog light, left
L13 L45	A 5	Front fog light, left / Daytime running light, left
L14	A 6	Front fog light, right
L14 L48	A 6	Front fog light, right / Daytime running light, right
L15	D 3	Work light
L15	D 5	Work light
L15	D 3	Work light
L17	D 4	Rolling beacon
L45	C 7	End out marker light
L46	C 6	End out marker light
L81	D 2	Splicing beacon
L83	C 8	Distance light
L84	C 8	Distance light
L84	C 6	ID-light
L84	C 7	ID-light
L85	C 6	ID-light
L85	C 7	ID-light
L86	C 6	ID-light
L86	C 7	ID-light
L139	D 2	Rolling beacon
L131	A 6	Category six lamp
L132	A 7	Category six lamp
L138	A 9	ChIPox lamp, front LH
L139	A 7	ChIPox lamp, front RH
L140	A 8	Headlamp, LH
L141	A 8	Headlamp, RH
L142	D 4	Rolling beacon
L145	A 5	Daytime running light, left
L146	A 5	Daytime running light, right
M7	A 6	Motor, windscreen washer
M8	A 6	Motor, hoodlamp washer
M21	A 6	Motor, light level control
M22	A 7	Motor, light level control
NS1V1	A 6	Signal horn
SP	F 3	Switch, rotating beacon
860	F 2	Switch, roof sign lighting
T138	F 6	Switch, 12-voltage



ID without switch ID with switch

Valid for headlamp type H4.
For Gasdischarge lamp see sheet 3.

1. Front Fog light
2. Daytime running light

Cavity C11.5 is occupied. See ECO 482372 & PCR 53997.

Valid for all roof heights except: High (See sheet 6)

S-order equipment connected: Cir dgm BOL



SCANIA

Circuit Diagram:

VIS

Drawing No.- Sheet-Rev: **1428523-2-32**

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden