



Colour code of electric cables	Code	Colour
BR	Black	
BN	Brown	
RD	Red	
OG	Orange	
YE	Yellow	
GN	Green	
BU	Blue	
VT	Violet	
GY	Grey	
WH	White	
PK	Pink	

Des.	Pos.	Description
C1	C3	Connector, 6P-pole
C2	F6	Connector, 21-pole
C3	E3	Connector, 21-pole
E4	E4	Connector, 21-pole
E2	E2	Connector, 21-pole
E7	E7	Connector, 5-pole
C11	E7	Connector, 21-pole, Inst-Roof
C29	E5	Connector 21-pole, Inst-Roof
C29	E3	Connector 21-pole, Inst-Roof
C29	E3	Connector 21-pole, Inst-Roof
C29	E6	Connector 21-pole, Inst-Roof
C29	E7	Connector 21-pole, Inst-Roof
C29	E8	Connector 21-pole, Inst-Roof
C34	F2	Connector, 21-pole
C94	F3	Connector, 21-pole
C94	F6	Connector, 21-pole
C100	C2	Connector, 6P-pole
C117	D7	Splice, sunvisor, VIS
C119	D7	Splice, sunvisor, VIS
C138	B6	Splice, bumper, VIS
C140A	D8	Splice, sunvisor, VIS
C140B	D8	Splice, sunvisor, VIS
C141	B5	Splice, sunvisor, VIS
C142	B5	Splice, sunvisor, VIS
C162	B2	Socket, 15-pole
C168	B5	Splice, bumper, VIS
C207	D4	Connector, 5-pole, VIS
C208	D2	Connector, 5-pole, VIS
C251	A4	Cut cable, VIS
C254	A5	Cut cable, VIS
C256	A4	Cut cable, VIS
C257	A5	Cut cable, VIS
C325	D5	Connector, 5-pole
C438	E6	Splice, sunvisor, VIS
C432	B2	Socket, 7-pole, 24N
G9	F2	Joint connector, ground
G9	F3	Joint connector, ground
G9	F6	Joint connector, ground
G10.E	E2	Ground, roof
G10.F	E3	Ground, roof
G10.F	E4	Ground, roof
G13.D	B2	Ground, topdeck wall
G16.A	E7	Ground, roof
G21.A	B6	Ground, cab front
G21.A	B8	Ground, cab front
G21.B	B8	Ground, cab front
G21.C	B7	Ground, cab front
G22.A	B7	Ground, cab front
G22.B	B7	Ground, cab front
G22.C	B5	Ground, cab front
L11	A5	Distance light
L12	A5	Distance light
L13	A5	Front fog light, left
L13.L45	A5	Front fog light, left / Daytime running light, left
L14	A6	Front fog light, right
L14.L46	A6	Front fog light, right / Daytime running light, right
L15	D3	Work light
L16	D5	Work light
L17	D4	Rotating beacon
L45	C7	End out marker light
L46	C8	End out marker light
L51	D2	Signal lamp
L63	C8	Distance light
L64	C8	Distance light
L65	D2	Rotating beacon
L84	C6	ID-light
L84	C7	ID-light
L85	C6	ID-light
L85	C7	ID-light
L86	C6	ID-light
L86	C7	ID-light
L100	D2	Rotating beacon
L121	A8	Category six lamp
L122	A7	Category six lamp
L138	A8	DirPos lamp, front LH
L139	A7	DirPos lamp, front RH
L140	A8	Headlamp, LH
L141	A7	Headlamp, RH
L142	D4	Rotating beacon
L145	A5	Daytime running light, left
L146	A6	Daytime running light, right
M7	A6	Motor, windscreen washer
M8	A6	Motor, headlamp washer
M21	A8	Motor, light level control
M22	A7	Motor, light level control
N2/C5	A6	Signal horn, air/ Connector, 2-pole
N2/C5	A6	Signal horn, air/ Connector, 2-pole
N17	A6	Signal horn, air
S59	F3	Switch, rotating beacon
S60	F2	Switch, roof sign lighting

Cable designation	
AWD35_OG - 1	Cable marking
	Cable colour (Change)
	Conductor area (mm ²)

Cavity C11:5 is occupied. See ECO 482372 & PCR 53997.

Valid for all roof heights except: High (See sheet 6)

S-order equipment connected: Cir dgm BCL

Valid for Halogen (H4) head lamp.
For Halogen (H7) & Gas discharge (Xenon) head lamp see sheet 8.

1. Front Fog light
2. Daytime running light

SCANIA

Circuit Diagram:

VIS

Drawing No. **1428523-2-34**
Sheet-Rev.

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden