


| Des | Pos | Description |
|-------|-----|--------------------------------------|
| B49 | C 6 | Switch, manual exhaust brake |
| C1 | E 5 | Connector, 66-pole |
| C69 | D 7 | Connector, 21-pole, instr pifront |
| RD | B 4 | Red |
| C100 | B 4 | Connector, 66-pole |
| OG | A 5 | Orange |
| C275 | C 7 | Joint connector, instr light |
| YE | A 5 | Yellow |
| GN | C 7 | Green |
| BU | D 6 | Blue |
| VT | D 2 | Joint connector green CAN |
| GY | D 3 | Joint connector red CAN |
| WH | D 2 | Joint connector yellow CAN |
| PK | D 2 | Joint connector yellow CAN |
| C482 | F 5 | Joint connector wake up |
| C482 | C 3 | Joint connector wake up |
| C483 | F 6 | Joint connector wake up |
| C489 | E 7 | Connector, 21-pole, BWS |
| D35 | E 5 | Potentiometer, throttle pedal sensor |
| D60 | E 5 | Potentiometer, clutch pedal |
| D61 | E 5 | Potentiometer, brake pedal |
| E30 | E 6 | Control unit, coordinator |
| E44 | A 4 | Control unit, EMS |
| E49 | D 3 | Control unit, immobiliser |
| G1 | C 2 | Joint connector, ground |
| G2 | B 7 | Joint connector, ground |
| G4 | C 6 | Joint connector, ground |
| G15.D | C 4 | Ground, torpedo wall |
| G15.H | E 4 | Ground, torpedo wall |
| K1 | C 1 | Diagnostics outlet |
| P2 | F 5 | Central electric unit |
| P2 | D 4 | Central electric unit |
| S4 | F 7 | Switch, starter |
| S6 | C 8 | Switch, exhaust brake power |
| S29 | C 7 | Switch, white smoke limiter |
| S51 | D 8 | Switch, cruise control/display |
| S142 | C 3 | Switch, cruise control |
| T3 | F 6 | Monitor, applied parking brake |
| T8 | C 7 | Monitor, coolant level |
| T16 | A 4 | Sensor, fuel level |
| T27 | D 5 | Sensor, outdoor temperature |
| U6 | E 8 | Spring coil |



SCANIA

Circuit Diagram:

COO

Drawing No.-
Sheet-Rev: **1441456-1-23**

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden

STD
4247