



Des.	Pos.	Description
C86	B 4	Connector, 3-pole
C92	B 8	Connector, Trailer
C100	C 8	Connector, 66-pole
C101	C 7	Connector, 66-pole
C102	C 3	Connector, 66-pole
C275	E 5	Joint connector, instr light
C480	E 7	Joint connector red CAN
C482	E 7	Joint connector wake up
E37	D 2	Control unit, ABS
G13	C 6	Ground, torpedo wall
G13	C 4	Ground, torpedo wall
G13.G	E 7	Ground, torpedo wall
G13.K	F 6	Ground, torpedo wall
G13.P	C 8	Ground, torpedo wall
F2	F 7	Central electric unit
S90	F 6	Switch, TC off
T11	B 7	Sensor speed, Front LH
T12	B 7	Sensor speed, Front RH
T13	B 6	Sensor speed, Rear LH
T14	B 5	Sensor speed, Rear RH
T28	B 4	Sensor speed, Add 1/6ch LH
T30	B 3	Sensor speed, Add 1/6ch RH
T96	B 4	Sensor, pressure EBL
V3	B 6	Pressure control valve, Front LH
V4	B 6	Pressure control valve, Front RH
V5	B 5	Pressure control valve, Rear LH
V6	B 5	Pressure control valve, Rear RH
V46	B 3	Pressure control valve, 6ch LH
V47	B 3	Pressure control valve, 6ch RH
V81	B 5	Solenoid valve, TC

Colour code of	Colour
BK	Black
BR	Brown
RD	Red
OR	Orange
YE	Yellow
GN	Green
BL	Blue
VT	Violet
WH	White
PK	Pink



Circuit Diagram:

BMS ABS

Drawing No - 1474798-1-8
Sheet-Rev:

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden