



Colour code of electric cables		Des.	Pos.	Description
Code	Colour	B16	A 8	Switch, reverse light
BK	Black	B45	A 8	Switch, neutral
BN	Brown	B87	B 5	Switch, acknowledge PTO EK
RD	Red	B88	B 5	Switch, acknowledge PTO EG
OG	Orange	C93	C 3	Connector, 7-pole, RET
YE	Yellow	C100	D 7	Connector, 66-pole
GN	Green	C101	D 8	Connector, 66-pole
BU	Blue	C102	D 3	Connector, 66-pole
VT	Violet	C112	C 7	Connector, 7-pole, manual Gearb/OPC
GY	Grey	C118	C 8	Connector, 4-pole, manual Gearb/OPC
WH	White	C429	C 4	Connector, 7-pole, RET
PK	Pink	C469	C 8	Connector, 4-pole
		C470	C 5	Connector, 4-pole
		C480	F 5	Joint connector red CAN
		C482	F 4	Joint connector wake up
		E5	E 5	Control unit, Opticruise
		E30.A	E 5	Control unit, coordinator
		F3	F 3	Joint connector, ground
		G13	C 5	Ground, torpedo wall
		G13	C 6	Ground, torpedo wall
		G13.N	C 8	Ground, torpedo wall
		G13.R	C 6	Ground, torpedo wall
		P2	F 4	Central electric unit
		T20	A 9	Sensor, tachograph
		T63	B 3	Sensor, water temp, retarder
		T80	B 3	Sensor, oil pressure, retarder
		T86	B 3	Sensor, oil temp, retarder
		V13	C 6	Solenoid valve, power take off EG
		V43	C 6	Solenoid valve, power take off EK
		V97	B 4	Solenoid valve unit, retarder
		V111	B 7	Solenoid valve unit, range/split

Manual gearbox

PTO

Retarder

SCANIA

Circuit Diagram:

GMS OPC4

Drawing No.-
Sheet-Rev: **1480737-1-6**

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden

STD
4247