



Des.	Pos.	Description
C600	5 E	Connector 21 Pole Instrument Panel
C650	7 C	Connector 21 Pole Front Axle
C660	6 C	Connector 21 Pole Driven Axle
C670	5 C	Connector 21 Pole Tag Axle
C680	2 C	Connector 21 Pole BCS Output
E18	4 D	Control unit: SMS
E510	8 B	Control unit: Tilt Switch
G500	4 F	Join Connector 21 pole Grounding Instrument Panel
P2	7 F	Central electric unit
T70	5 B	Sensor: pressure, rear left
T72	7 B	Sensor: distance, front
T73	6 B	Sensor: distance, rear left
T97	5 B	Sensor: distance, rear right
T98	5 B	Sensor: pressure, rear right
T99	6 B	Sensor: pressure, front axle
T507	5 F	Pressure sensor, for ELC System total
V524	7 B	Solenoid Valve, Front Axle up/down
V524	6 B	Solenoid Valve, Driven Axle
V525	4 B	Solenoid Valve, Tag Axle up/down
V526	7 B	Solenoid Valve, Front Axle Kneeling

Cable designation		Colour code of sensor cables	
AWG035 - OG - 1		Code	Colour
Cable marking		BK	Black
Cable colour (Orange)		BN	Black
Conductor area (mm ²)		BN	Black
		RD	Red
		OG	Orange
		YE	Yellow
		GN	Green
		BL	Blue
		VT	Violet
		GY	Grey
		WH	White
		PK	Pink

SCANIA

Circuit Diagram:

SMS ELC

Drawing No. - 1540003-1-4
Sheet-Rev:

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden

STD 4247