



Des	Pos	Description
C170	B 3	Connector, 1-pole
C171	B 3	Connector, 1-pole
C500	C 5	Connector 21 Pole, instrument lights
C506	D 7	Join Connector 21 Pole CAN Yellow
C600	E 7	Connector 21 Pole Instrument Panel
C602	E 3	Connector 21 Pole Visibility
C603	E 7	Connector 21 Pole COO
C630	E 3	Connector, 18 pole, Engine
C650	E 5	Connector 21 Pole Front Axle
D35	A 7	Potentiometer, throttle pedal sensor
D60	A 7	Potentiometer, clutch pedal
E30	D 3	Control unit, coordinator
G49	A 3	Ground, component
G501	C 4	Join Connector 21 pole Grounding
G504	E 3	Join Connector 21 pole Grounding Electric Centre
K1	D 6	Diagnostics outlet
P2	F 6	Central electric unit
S4	D 7	Switch, starter
S6	B 6	Switch, exhaust brake power
S26	B 3	Switch, signal horn
S29	B 5	Switch, white smoke limiter
S51	A 4	Switch, cruise control/display
S142	B 5	Switch, cruise control
S524	B 6	Switch, Fixed raised idling speed
T3	B 7	Monitor, applied parking brake
T16	F 5	Sensor, fuel level
T27	B 6	Sensor, outdoor temperature
T501	B 6	Sensor, Parking brake applied
U6	B 3	Spring coil

Cable designation		Colour code of electric cables	
AWD35	OG - 1	Code	Colour
		BK	Black
		BN	Brown
		RD	Red
		OG	Orange
		YE	Yellow
		GN	Green
		BU	Blue
		VT	Violet
		GY	Grey
		WT	White
		PK	Pink

SCANIA

Circuit Diagram:

COO

Drawing No.-
Sheet-Rev: **1540009-1-7**

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden

STD
4247