



Des	Pos	Description
B16	A 5	Switch, reverse light
B45	A 5	Switch, neutral
C123	B 4	Splice, 1-pole
C202	B 5	Splice, gearbox
C498	C 4	Connector, 7-pole
C681	F 5	Connector 21 Pole Instrument Panel
C640	E 5	Connector 21 Pole Gearbox
C740	C 8	Connector, 7-pole, retarder
C741	C 5	Connector, 4-pole, gearbox
E5	D 6	Control unit, Opticourse
G504	F 6	Join Connector 21 pole Grounding Electric Centre
P2	F 7	Central electric unit
T20	A 4	Sensor, tachograph
T63	A 7	Sensor, water temp, retarder
T60	A 7	Sensor, oil pressure, retarder
T86	A 7	Sensor, oil temp, retarder
V63	A 4	Solenoid valve, low range
V78	A 4	Solenoid valve, high range
V97	A 6	Solenoid valve unit, retarder

Cable designation		Colour code of electric cables	
Code	Colour	Code	Colour
AWD35_OG - 1		BN	Brown
		BL	Black
		RD	Red
		OR	Orange
		YS	Yellow
		GN	Green
		BU	Blue
		VT	Violet
		GR	Grey
		WH	White
		PK	Pink

SCANIA

Circuit Diagram:

GMS OPC4 GR801R

Drawing No.- 1540011-2-4
Sheet-Rev:

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden

Manual gearbox STD 4247