



Code	Colour
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink

Des.	Pos.	Description
C121	C 2	Connector, 2-pole
C4000	D 2	Connector, 4-pole, Diagnostics
C4001	D 4	Connector, 8-pole, Interface
C4001	D 2	Connector, 8-pole, Interface
C4001	B 2	Connector, 8-pole, Interface
C4002	D 4	Connector, 6-pole, Interface
C4002	D 4	Connector, 6-pole, Interface
C4002	B 4	Connector, 6-pole, Interface
C4002	D 4	Connector, 6-pole, Interface
C4003	C 2	Splice, 1-pole, Interface
C4004	C 2	Splice, 1-pole, Interface
C4005	C 2	Splice, 1-pole, Interface
C4006	C 2	Splice, 1-pole, Interface
C4007	C 4	Connector, 3-pole
C4008	A 4	Connector, 4-pole
C4008	A 5	Connector, 4-pole
C4008	A 5	Connector, 4-pole
E44	C 2	Control unit, EMS
H15	B 2	Heater, fuel filter
M1	B 5	Starter motor
P3	B 6	Alternator
T5	D 6	Sensor, oil press, oil temp engine
T8	B 3	Monitor, coolant level
T33	D 6	Sensor, coolant temperature
T75	D 3	Sensor, engine speed 1
T74	D 3	Sensor, engine speed 2
T110	B 4	Sensor, oil level
T111	D 3	Sensor, pressure, rail
T123	B 5	Sensor, fan control, fan speed
T135	D 5	Sensor, phase
T4000	D 5	Sensor, pressure, atmosphere
V109	D 4	Solenoid valve, Wastegate
V120	B 5	Solenoid valve, inlet metering

SCANIA

Circuit Diagram:

EMS 8-cyl XPI

Drawing No.-
Sheet-Rev: **1764884-1-6**

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden