



Des.	Pos.	Description
C600	5 E	Connector 21 Pole Instrument Panel
C650	1 C	Connector 21 Pole Front Axle
C660	6 C	Connector 21 Pole Driven Axle
C670	5 C	Connector 21 Pole Tag Axle
C690	2 C	Connector 21 Pole BCS Output
E18	4 D	Control unit - SMS
E510	8 B	Control unit - TR Switch
G500	4 F	Join Connector 21 pole Grounding Instrument Panel
P2	7 F	Central electric unit
T70	5 B	Sensor, pressure, rear left
T72	7 B	Sensor, distance, front
T73	6 B	Sensor, distance, rear left
T97	5 B	Sensor, distance, rear right
T98	5 B	Sensor, pressure, rear right
T199	6 B	Sensor, pressure, front axle
T507	5 F	Pressure sensor, for ELC System total
V523	7 B	Solenoid Valve - Front Axle Up/down
V524	6 B	Solenoid Valve - Driven Axle
V525	4 B	Solenoid Valve Tag Axle Up/down
V526	7 B	Solenoid Valve - Front Axle Knurling

Cable designation		Colour
AWD35 - OG - 1		Orange
Cable marking		
BN		Black
BR		Brown
RD		Red
OG		Orange
YE		Yellow
GN		Green
BL		Blue
VT		Violet
GY		Grey
WH		White
PK		Pink

SCANIA

Circuit Diagram:

SMS ELC

Drawing No.- 1790750-2-10
Sheet-Rev:

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden