



Code	Colour
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink

Des.	Pos.	Description
C121	A 6	Connector, 2-pole
C4000	D 6	Connector, 4-pole, Diagnostics
C4001	A 5	Connector, 8-pole, Interface
C4001	D 5	Connector, 8-pole, Interface
C4001	D 5	Connector, 8-pole, Interface
C4002	A 4	Connector, 6-pole, Interface
C4002	D 4	Connector, 6-pole, Interface
C4002	A 5	Connector, 6-pole, Interface
C4002	A 3	Connector, 6-pole, Interface
C4002	A 5	Connector, 6-pole, Interface
C4002	A 4	Connector, 6-pole, Interface
C4002	A 5	Connector, 6-pole, Interface
C4002	D 4	Connector, 6-pole, Interface
C4003	C 5	Splice, 1-pole, Interface
C4004	C 5	Splice, 1-pole, Interface
C4005	C 5	Splice, 1-pole, Interface
C4006	C 5	Splice, 1-pole, Interface
C4009	B 3	Connector, 6-pole
C4010	B 4	Connector, 3-pole
C4016	B 5	No Description
C4017	B 5	No Description
C4018	A 5	No Description
D4000	A 5	Resistor, EGR
E44	B 1	Control unit, EMS
H15	B 6	Heater, fuel filter
M1	B 4	Starter motor
M28	A 4	Motor, electrical actuator EGR 1
P3	B 4	Alternator
T5	B 1	Sensor, oil press, oil temp engine
T8	B 2	Monitor, coolant level
T33	D 2	Sensor, coolant temperature
T47	D 1	Sensor, charger pressure/temp
T74	D 3	Sensor, engine speed 1
T75	D 2	Sensor, engine speed 2
T123	B 3	Sensor, fan control, fan speed
T4001	B 1	Sensor, oil press, oil temp engine
V109	D 3	Solenoid valve, Wastegate

1) Option PDE Injection, 5-cyl.: See sheet 2
 Option PDE Injection, 6-cyl.: See sheet 3

SCANIA

Circuit Diagram:

Drawing No.- 1867139-1-6.iso
 Sheet-Rev:

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden