



Des.	Pos.	Description
C45	A 7	Connector, 4-pole
C46	A 6	Connector, 4-pole
C99	C 7	Connector, 4-pole
C430	C 7	Connector, 7-pole
C462	D 5	Connector, 3-pole
C632	E 7	Connector, 15-pole, APS, FHS, EEC
C820	D 7	Connector, 21-pole
C832	D 7	Connector, 15-pole, APS, FHS, EEC
E67	B 5	Control unit, EEC
G504	F 6	Joint Connector, 21 pole, Grounding Electric panel
P2	F 6	Central electric unit
R660	F 7	Relay, Power supply EMS S6+EEC
R661	F 7	Relay, Timer for R660
T113	A 6	Sensor, temp, upstream
T115	A 7	Sensor, nox - Downstream
T116	A 6	Sensor unit, temperature/level
V117	A 5	Dosing unit
V118	A 5	Water valve, EEC

Cable designation		Colour code of electric cables	
AWD35	OG - 1	Code	Colour
Cable marking		BK	Black
Cable colour (Orange)		BN	Brown
Conductor area (mm ²)		RD	Red
		OG	Orange
		YE	Yellow
		GN	Green
		BU	Blue
		VT	Violet
		GY	Grey
		WH	White
		PK	Pink

Circuit Diagram:

EEC

Drawing No.- 1910151-2-5
 Sheet-Rev:

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden

Valid for K 6x2/2