



Des.	Pos.	Description
C690	G 5	Connector 21 Pole BCS Output
C6101	C 5	Connector, 3 pole
C6103	E 5	Connector, 3 pole
C6104	G 4	Connector, 3 pole
C6105	G 4	Connector, 6 pole
C6106	C 4	Connector, 2 pole
C6107	C 3	Connector, 2 pole
C6108	C 3	Connector, 2 pole
C6109	C 2	Connector, 2 pole
C6110	C 2	Connector, 2 pole
C6111	C 2	Connector, 2 pole
D6004	C 7	Diode unit, fire extinguishing system DD
E6006	A 8	Control unit, Node 2.2
E6011	A 6	Control unit, fire extinguishing system DD
G6009	C 5	Ground, 1 pole

Cable designation	
AWD35 . OG - 1	
Cable marking	
Cable colour (Orange)	
Conductor area (mm <sup>2</sup> )	

Colour code of electric cables	
Code	Colour
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink

Assembly	Description	Issue	Variants	Variables
2051927			OPT1	
2051928			OPT2	
Com2051927			Common	
Com2051928			Common	

See wir dgm ICL2 DD (C3146)

See wir dgm power supp std equipment DD (C2874)

See cir dgm BCS

**SCANIA**

Circuit Diagram:  
**Fire Extinguishing Equipment DD**

Drawing No.-  
Sheet-Rev: **2051925-1-1**

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden