



**Cable designation**

AWD35 OG - 1

Cable marking

Cable colour (Orange)

Conductor area (mm<sup>2</sup>)

| Code | Colour | Des.      | Pos. | Description                              |
|------|--------|-----------|------|--|
| C3   |        | A 5       |      | Connector, 21-pole                       |
| C12  |        | D 3       |      | Connector, 21-pole                       |
| BK   | Black  | D 2       |      | Connector, 21-pole                       |
| BN   | Brown  | C 5       |      | Connector, 21-pole                       |
| RD   | Red    | B 7       |      | Connector, 21-pole                       |
| OG   | Orange | C 479     | F 7  | Joint connector green CAN                |
| YE   | Yellow | C 483     | F 5  | Joint connector wake up                  |
| GN   | Green  | C 8002    | F 6  | Joint connector, second wake up          |
| BU   | Blue   | C 8016    | A 4  | Connector, 21-pole                       |
| VT   | Violet | C 8023    | B 5  | Splice, INL, Roof shelf                  |
| GY   | Grey   | C 8024    | B 5  | Splice, INL, Roof shelf                  |
| WH   | White  | C 8025    | D 3  | Splice, INL, Instr                       |
| PK   | Pink   | C 8040    | D 7  | Splice, INL, Instr                       |
|      |        | C 8043    | D 7  | Splice, INL, Instr                       |
|      |        | C 8056    | F 7  | Splice, B                                |
|      |        | C 8080-1  | C 3  | Splice, instr light                      |
|      |        | C 8118    | E 7  | Cut cable, CAN shield, E23               |
|      |        | E 23      | E 4  | Control unit, general lighting exclusive |
|      |        | G 4-2     | F 8  | Splice, ground                           |
|      |        | G 8-3     | B 3  | Splice, ground                           |
|      |        | G 64-2    | B 4  | Splice, ground                           |
|      |        | G 65-2    | B 5  | Splice, ground                           |
|      |        | L 54      | A 7  | Headlining lamp, driver                  |
|      |        | L 55      | A 8  | Headlining lamp, passenger               |
|      |        | L 176     | C 7  | Light below IP                           |
|      |        | L 177     | C 7  | Light below IP                           |
|      |        | L 178     | C 6  | Light below IP                           |
|      |        | L 179     | C 6  | Light below IP                           |
|      |        | L 180     | D 5  | Light IP centre                          |
|      |        | L 180     | C 7  | Light IP centre                          |
|      |        | L 181     | A 6  | Light below roof shelf centre            |
|      |        | L 192     | A 6  | Light below roof shelf centre            |
|      |        | P 2.BX 20 | F 4  | Fuse socket, CEU                         |
|      |        | S 79      | C 3  | Switch, general light exclusive bed      |

INL Standard

Note:  
 1. INL Standard WO background light  
 2. Crew cab only

**SCANIA**

Circuit Diagram:

**INL**

Drawing No.-  
Sheet-Rev: **2125404-2-13**

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden