Des.	Pos.	Description
C2.A	A 3	Connector, 2-pole
C2.B	A 3	Connector, 2-pole
C2.C	A 3	Connector, 2-pole
C2.D	A 2	Connector, 2-pole
C193	C 7	Connector, 16-pole
C227	A 5	Connector, 16-pole
C318	C 7	Connector, 4-pole
C436	A 7	Connector, 12-pole
C443	A 5	Connector, 21-pole
C640	D 6	Connector 21 Pole Gearbox
C641	D 5	Connector, 9 pole HEV
C712	D 3	Connecter, 5 pole HEV +24V
C713	D 2	Connecter, 2 pole HEV Ground
C773	C 7	Joint connector GMS SUB-CAN
C798	B 6	Connector, 3 pole HEV
C904	D 5	Connector, 18 pole HEV
E5	D 6	Control unit, Opticruise
E81	B 5	Control unit, BMU
E82	B 7	Control unit, MGU
F552	E 6	Fuse holder, 4-pole, Electric panel, Gas
F563	E 4	Fuse holder 4 pole HEV
F564	C 3	Fuse holder 4 pole HEV
G502.C	D 2	Grounding Hybrid system on Front Axle
G504	D 6	Joint Connector, 21 pole, Grounding Electric panel
G6042	D 2	Ground, 1-pole
G6043	D 2	Ground, 1-pole
M33	A 8	Motor, propulsion
P2	F 4	Central electric unit
P7	E 8	Electric unit
R500	E 3	Relay, Battery master switch
S229	D 4	Switch, Interlock loop control

Cable designation

AWD35 . OG - 1

Cable marking

Cable colour (Orange)

Conductor area (mm²)

Colour code of electric cables	
Code	Colour
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink

See circuit diagram 2198982

See circuit diagram 2098187

*1 GMS OPC4
*2 GMS G5

SCANIA

Circuit Diagram:

HEV

Drawing No.-
Sheet-Rev: 2164280-1-9

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden