

Cable designation

AWD35 . OG - 1

Cable marking

Cable colour (Orange)

Conductor area (mm²)

Colour code of electric cables	
Code	Colour
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink

Des.	Pos.	Description
B11	B 7	Switch, diff lock, axle
B12	B 7	Switch, diff lock, second axle
B13	B 7	Switch, diff lock, tandem
C101	E 3	Connector, 72-pole
C294	E 7	Joint connector, orange CAN, forward position
C8074	E 6	Connector, 2-pole
C8090	B 7	Joint connector, Sub CAN, CMS
C8156	E 5	Connector, 4-pole
C8236	C 4	Cut cable
E113	C 3	Control unit, CMS
E129	D 4	Battery equalizer
G33	E 6	Ground
M55	E 6	Motor, dual circuit steering
P8	E 8	Central electric unit, chassis
P11	F 6	Power distributor, chassis
R94	D 4	Relay, ADR, battery switch
R105	D 4	Relay, starter battery
T16	D 7	Sensor, fuel level
T55	F 6	Monitor, flow, circuit 1
T56	F 5	Monitor, flow, circuit 2
T70	B 5	Sensor, pressure, rear left
T73	B 6	Sensor, distance, rear left
T180	D 7	Sensor, steering fluid
T226	B 7	Sensor, fuel level
V10	B 8	Solenoid valve, diff lock, axle
V11	B 8	Solenoid valve, diff lock, tandem
V32	B 6	Solenoid valve, disengage front spring brake
V54	B 4	Solenoid valve, up/down
V54	B 5	Solenoid valve, up/down

1) Left hand drive.
2) Right hand drive.
3) Level adjustment speed basic
4) Level adjustment speed fast

SCANIA

Circuit Diagram:

CMS

Drawing No.-
Sheet-Rev: 2202966-1-36

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden