


Code	Colour	Des.	Pos.	Description
B11	B7	Switch, diff lock, axle		
B12	B7	Switch, diff lock, second axle		
B13	B7	Switch, diff lock/dog clutch, tandem		
BN	Brown			
RD	Red			
OG	Orange			
YE	Yellow			
GN	Green			
BU	Blue			
VT	Violet			
GY	Grey			
WH	White			
PK	Pink			



- Notes:**
- 1) Left hand drive
 - 2) Right hand drive
 - 3) Level adjustment speed basic
 - 4) Level adjustment speed fast
 - 5) Electrical system generation 6 or Battery Electric vehicle (BEV3)
(Electrical system generation 6 = Vehicle with Coordinator system 8 or 10)
 - 6) Electrical system generation 7. Not valid for Battery Electric vehicle (BEV3)
(Electrical system generation 7 = Vehicle with Coordinator system 11)
 - 7) Without Battery monitor
 - 8) With Battery monitor
 - 9) Not valid for Battery Electric vehicle (BEV3). For BEV3, see Sheet 2
 - 10) C100: Without AWD, EPB, EST, ESTA, TPM
 - 11) TPM: Without AWD, EPB, EST, ESTA. With TPM
 - 12) C295: With Any/Some/All AWD, EPB, EST, ESTA
 - 13) C295-1: With Either EPB, EST, AWD
 - 14) C295-2: With (EST, ESTA) or With (EPB and Either AWD, EST)
 - 15) MCC_1: With Steering backup: hydraulic.
- Valid for vehicle with Combustion engine
 16) MCC_22: With Battery pos.: RHS, Battery master switch auto.
 Valid for Battery Electric vehicle (BEV1)
 (MCC_1 and MCC_22 cannot come together)

SCANIA

Circuit Diagram:

CMS

Drawing No.-
Sheet-Rev: **2202966-1-52**

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden

S-order equipment connected