


Des.	Pos.	Description
C621	E 7	Connector, 36-pole Elec.pan/Frame
C701	E 7	Connector, 62 pole
C802	E 4	Connector, 62 pole
E18	F 4	Control unit, SMS
E504	D 4	Control unit, SMS
G505-2	F 7	Splice ground
P2 BX62	F 7	Fuse socket, central electric unit
P8	F 5	Central electric unit, chassis
T72	A 6	Sensor, distance, front
T99	A 6	Sensor, pressure, front
T543	B 5	Sensor, distance middle axle left
T544	B 5	Sensor, distance middle axle right
T761	B 5	Sensor, pressure Middle axle left
T762	B 4	Sensor, pressure Middle axle right
V523	A 7	Solenoid Valve, Front Axle up/down
V526	A 6	Solenoid Valve, Front Axle Kneeling
V543	B 5	Solenoid valve, Middle axle



Code	Colour
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink



Circuit Diagram:

SMS ELC4

Drawing No.- 2275948-2-7
Sheet-Rev:

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden

Valid for Articulation