


Des.	Pos.	Description
C621	E 8	Connector, 36-pole
C703	D 6	Connector 62 pole
C802	E 6	Connector, 62 pole
C803	E 4	Connector, 62 pole
E18	D 2	Control unit, SMS
E504	D 6	Control unit, SMS
G505	F 7	Ground, Join connector 21-Pole Electric Panel
P2.BX62	F 8	Fuse socket, central electric unit
P8	F 6	Central electric unit, chassis
T70	B 4	Sensor, pressure, rear left
T72	B 7	Sensor, distance, front
T73	B 4	Sensor, distance, rear left
T97	B 3	Sensor, distance, rear right
T98	B 3	Sensor, pressure, rear right
T99	B 7	Sensor, pressure, front
T543	B 6	Sensor, distance middle axle left
T544	B 6	Sensor, distance middle axle right
T761	B 6	Sensor, pressure Middle axle left
T762	B 6	Sensor, pressure Middle axle right
V523	B 8	Solenoid Valve, Front Axle up/down
V524	B 4	Solenoid Valve, Driven Axle
V526	B 8	Solenoid Valve, Front Axle Kneeling
V543	B 7	Solenoid valve, Middle axle



Colour code of electric cables	
Code	Colour
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink

SCANIA

Circuit Diagram:

SMS

Drawing No.-
Sheet-Rev: **3093912-2-5**

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used or brought to the attention of any third party without prior permission (C) Scania, Sweden

Valid for Articulation